

SKU	Description	Gear Ratio	Unloaded RPM		Unloaded Current (mA)		Stall Current (mA)		Stall Torque (gm*cm)		Dimensions (mm)		
			3V	6V	3V	6V	3V	6V	3V	6V	Length	Width	Height
GM2	Offset/Inline	224:1	24	46	40	50	400	NA	3500	4100	55.0	48.0	22.7
GM3	90 Degree	224:1	24	46	40	50	400	NA	3500	4100	70.1	37.7	22.3
GM4	Servo Body	325:1	67	77	64	93	322	529	2529	3668	46.6	55.4	20.0
GM6	Mini Offset/Inline	120:1	64	157	64	97	326	563	972.1	1519.3	36.5	40.7	24.7
GM7	Mini 90 Degree	120:1	75	146	80	92	310	524	981	1712.4	58.0	22.3	24.8
GM8	Offset/Inline	143:1	40	78	50	52	400	700	3200	5500	53.8	47.8	22.9
GM9	90 Degree	143:1	40	78	50	52	400	700	3200	5500	70.2	30.4	22.6
GM10	Centering Pager Gearmotor	81:1	233	454	13	20	118	220	158.5	228.3	20.8	29.0	25.4
GM11a	Metal Gearhead	56.8:1	181	370	28	42	428	760	427	441	34.3	12.0	10.1
GM12a	Metal Gearhead	100:1	85	169	18	32	290	456	1120	1960	30.4	12.0	10.1
GM13a	Metal Gearhead	150:1	58	109	32	38	258	480	1344	2268	33.0	12.0	10.1
GM14a	Metal Gearhead	298:1	33.3	75	40	50	456	830	1638	3234	35.2	12.0	10.1
GM15	Pager Gear Motor	25:1	920	1550	100	200	210	350	35.28	69.3	20.1	6.0	6.0
GM17	Centered 3mm output shaft	228:1	12	30.6	16	24	253	492	3135.9	6011.4	51.7	27.3	37.2
GM18	Metal Gearhead	30:1	297	556.6	32	54	292	528	256.2	387.8	34.0	12.0	10.1
GM19	Metal Gearhead	35:1	385	706	112	176	1156	2128	541.8	674.8	36.4	16.0	16.0
GM20	Metal Gearhead	100:1	120	240	34	70	612	948	1526	2716	34.0	14.0	14.0
GM21	Metal Gearhead	360:1	11	23	38	42	360	692	3570	7434	49.3	15.5	15.5
GM22	Metal Gearhead	298:1	39	79	44	64	608	948	2534	3444	34.0	14.0	14.0



Solarbotics Ltd.
201 35th Ave NE
Calgary, AB T2E 2K5
Canada

North America Toll Free: 1-866-276-2687
Local / International: 1-403-232-6268
Fax: 1-403-226-3741
www.solarbotics.com