



P.C. MOUNTING

Model No.	POS.1	POS.2	POS.3
SMS1	ON	NONE	ON
Term. Comm.	2-1	N/A	2-3
SCHEMATIC		N/A	

SWITCH FUNCTION

SPECIFICATIONS
MECHANICAL LIFE: 30,000 make-and-break cycles.
CONTACT RESISTANCE: 10mΩ max. initial @ 2-4VDC
 100mA for both silver and gold plated contacts.
INSULATION RESISTANCE: 1,000MΩ min.
DIELECTRIC STRENGTH: 1,000 V RMS@sea level.
OPERATING TEMPERATURE: -30°C to 85°C.

MATERIALS
CASE: Dially phthalate (DAP) (UL 94v-0).
ACTUATOR: Nylon, black std.
HOUSING: Stainless Steel.
CONTACT: Silver or gold plated.
TERMINAL SEAL: Epoxy.
ROHS: 2002/95/EC

RATING :
 R : 0.4 Volt-Amps(VA) max. @20V max.(AC or DC)
 Q : 2Amps @250VAC
 5Amps @120 VAC or 28 VDC

JCJ INTERNATIONAL CO., LTD

符號	原尺寸	修改後尺寸	變更日期	
1	(A)	8.90(.350)	9.30(.366)	MAY-14-2010
2	(B)			
3	(C)			
4	(D)			
5	(E)			

SCALE (比例) : 3 : 2

TOLERANCE (公差) :
 0.00 mm ± 0.25mm
 0.0 mm ± 0.40mm
 ANGULAR : ± 5°

FILE NAME : 5MSP0139

TITLE	Slide Switches	SIZE
圖名		圖紙
DWG NO.	5MS1S102AVS2QES	A4
圖號		UNIT
REV.	B	單位
版本	DATE	inch
CHECKED BY	JUL - 20 - 2005	mm
審核	D.H.	SHEET
		張數
		1 of 1
		DRAWN BY
		製圖
		CINDY